

LASERLINER - VideoFlex G3 ArcView – 092.914A

Website Title

Laserliner 9mm Probe articulating Inspection Camera, 1m probe length, 320 x 240 pixels (Display), 640 x 480 pixels resolution (Camera), LED

Product Details

Laserliner VideoFlex G3 ArcView Inspection Camera

Laserliner VideoFlex G3 ArcView is a recordable inspection camera with an manual articulating viewing camera with a maximum adjustment up to 130 degrees. The camera probe is interchangeable and come with a 9mm head. The camera probe is fully flexible, waterproof (IP67) and come with a good depth of field and with 4 high intensity LED lights.

The Hand held camera unit has a large 3.5 in TFT colour display with 1.5 x digital zoom and 180 degree picture rotation. It has record function for video, still pictures and webcam onto an 8 GB max SDHC card.

Features and Benefits

Camera Head 9mm
Camera Focus front 3cm – 5cm
Adjustable head flexibility from 0 - 130 degrees
Field of view 57 degrees
Minimum bend radius 50mm
High performance 4 x LED
Waterproof camera head IP67
Camera Screen 3.5in TFT
Recording Function
Webcam Function
TV out connection
SDHC Memory compatible
Compatible with VideoFlex G3 & G4 models

Contents:

Video Inspection recordable with ArcView camera 1M, 9mm camera head, Li-ion battery, IP67 waterproof, Mini SD Card, Hard Case, 40 x cleaning wipes, Pocket LED flashlight. (Exclusive RS)

Technical data

VideoFlex G3 - Display

SCREEN TYPE	3.5" TFT colour display
RESOLUTION DISPLAY	320 x 240 pixel
FORMAT PICTURE / FORMAT VIDEO	JPEG / AVI
ZOOM	1.5 x digital zoom in 10% steps
MEMORY	Supports up to max. 8 GB SDHC card
PORT	Mini USB
CONNECTIONS	Micro-SD, Analog-video
POWER SUPPLY	Li-Ion pack battery 3.7V / 1.7Ah / 5V / 1A power supply unit
CHARGING TIME	approx. 4 h
OPERATING TIME	approx. 4 h
OPERATING TEMPERATURE	0 °C ... 45 °C
STORAGE TEMPERATURE	-10 °C ... 60 °C

ArcView - Camera Probe

CAMERA RESOLUTION	640 x 480 pixels
CAMERA HEAD LEDS	4
CAMERA HEAD PROTECTION CLASS	water-resistant, IP 67
CAMERA HEAD	∅ 9 mm
CAMERA TYPE	CMOS image sensor
DIMENSIONS (W X H X D)	1120 mm x 39 mm x 38 mm
STORAGE CONDITIONS	-10°C ... 60°C, max. humidity 80% rH
OPERATING CONDITIONS	0°C ... 45°C, max. humidity 20 ... 90% rH, no condensation, max. working altitude 4000 m above sea level
MINIMUM BENDING RADIUS	100 mm
LENGTH OF FLEX CABLE	1 m
CABLE DIAMETER	7,6 mm
CAMERA FOCUS	F3 cm - F5 cm
FIELD OF VIEW (FOV)	57°
TOTAL WEIGHT	2500g (In hard case)

