



### Main

Range	TeSys
Product name	TeSys island
Device short name	TPRVM
Product or component type	Voltage interface module
Device presentation	Monitoring of the mains voltage powering the island Reporting of the voltage to the bus coupler to enable power & energy monitoring
Function of module	Monitoring of voltages in single phase systems L-N or L-L Monitoring of voltages in 3-phase systems without neutral N connection Calculation of RMS phase voltages, voltage phase sequence, fundamental frequency Identification of dip and swell events level and duration
Product compatibility	TPRBC bus coupler
[Ue] rated operational voltage	690 V AC 47...63 Hz
[Ui] rated insulation voltage	690 V conforming to IEC 61010-1
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 61010-1
Overvoltage category	III
Monitoring type	Phase voltage 100...690 V Phase frequency 47...63 Hz Phase sequence
Measurement accuracy	Voltage: +/- 5 %, Frequency: +/- 1 Hz,
Local signalling	1 LED (green/red)DS (device status): 1 LED (green/red)VS (voltage status):

### Complementary

[Us] rated supply voltage	24 V DC supplied by the bus coupler
Current consumption	2 mA
Power dissipation in W	0.5 W maximum
Standards	IEC 61010-2-201 UL 61010-2-201 CSA C22.2 No 61010-2-201
Product certifications	CSA UL EAC (pending)
Mounting mode	Horizontal and vertical (35 mm symmetrical rail)
Connections - terminals	Measuring input: removable spring terminal block 3 cable(s) 0.2...2.5 mm <sup>2</sup> (AWG 24...AWG 14) rigid Measuring input: removable spring terminal block 3 cable(s) 0.2...2.5 mm <sup>2</sup> (AWG 24...AWG 14) flexible without cable end Measuring input: removable spring terminal block 3 cable(s) 0.25...2.5 mm <sup>2</sup> (AWG 22...AWG 14) flexible with cable end
Width	25 mm
Height	118 mm
Depth	114 mm
Net weight	0.159 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Ambient air temperature for storage	-25...70 °C
Ambient air temperature for operation	-10...60 °C
Relative humidity	5...95 %
Operating altitude	0...2000 m without derating
IP degree of protection	IP20
Pollution degree	2
Protective treatment	TC
Fire resistance	960 °C conforming to UL 94
Shock resistance	15 gn (duration = 11 ms) conforming to IEC 60068-2-27
Vibration resistance	1.5 mm peak to peak (f= 3...13 Hz) conforming to IEC 60068-2-6 1 gn (f= 13...200 Hz) conforming to IEC 60068-2-6
Electromagnetic compatibility	Electrostatic discharge, level 3, 8 kV air, 6 kV contact, conforming to EN/IEC 61000-4-2 Radiated RF fields, level 3, 10 V/m, conforming to EN/IEC 61000-4-3 Line voltage circuit: fast transients immunity test, level 3, 2 kV, conforming to EN/IEC 61000-4-4 Line voltage circuit: surge immunity test (common mode), level 3, 2 kV, conforming to EN/IEC 61000-4-5

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	240 g
Package 1 Height	6.5 cm
Package 1 width	13.5 cm
Package 1 Length	15.5 cm

## Offer Sustainability

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------