



Main

Range of product	Acti 9
Device short name	IC2000P+
Product or component type	Programmable twilight switch with time switch function
Battery type	Lithium
Function available	Automatic time changeover Coupling with time switch functions
Language	Dutch English Finnish French German Italian Portuguese Spanish Swedish
Type of setting	Weekly programming

Complementary

Device application	Building
Measurement accuracy	< +/- 1 s/day
Number of channels	1
Control type	By brightness detection
Provided equipment	Wall-mounted cell
Load type	Parallel-corrected mercury and sodium vapour lamps, (250 VA) Fluorescent tube, balast : electronic, (9 x 36 W) Fluocompact lamp, balast : electronic, (9 x 7 W) Fluocompact lamp, balast : electronic, (7 x 20 W) Fluocompact lamp, balast : electronic, (7 x 15 W) Fluocompact lamp, balast : electronic, (7 x 11 W) Parallel-corrected fluorescent tube, balast : conventional, (6 x 58 W) Fluorescent tube, balast : electronic, (6 x 58 W) Dual mounted fluorescent tube, balast : electronic, (5 x (2 x 36 W)) Dual mounted fluorescent tube, balast : conventional, (10 x 100 W) Dual mounted fluorescent tube, balast : conventional, (26 x 36 W) Dual mounted fluorescent tube, balast : electronic, (3 x (2 x 58 W)) Serial-corrected fluorescent tube, balast : conventional, (26 x 36 W) Non-corrected fluorescent tube, balast : conventional, (26 x 36 W) Serial-corrected fluorescent tube, balast : conventional, (20 x 58 W) Non-corrected fluorescent tube, balast : conventional, (20 x 58 W) Parallel-corrected fluorescent tube, balast : conventional, (2 x 100 W) Serial-corrected fluorescent tube, balast : conventional, (10 x 100 W) Parallel-corrected fluorescent tube, balast : conventional, (10 x 36 W) Non-corrected fluorescent tube, balast : conventional, (10 x 100 W) Dual mounted fluorescent tube, balast : conventional, (20 x 58 W) 230 V AC incandescent lamp, (2300 W) 230 V AC halogen lamp, (2300 W)
Power consumption	3 VA
Maximum switching current	16 A - 250 V AC pf = 1 10 A - 250 V AC pf = 0.6
[Ue] rated operational voltage	230 V (+10 % -15 %) AC 50/60 Hz
Display type	Backlit LCD
Time delay	80 s (by default) 20 s to 140 s (on contact breaking) 20 s to 140 s (on closing)
Maximum number of switchings	42
Minimum interval duration	1 min
Backup time	5...6 years time and program saving

Mounting support	DIN rail
9 mm pitches	5
Light intensity adjustment	2...50 lux 350...2100 lux 60...300 lux
Connections - terminals	X 1 screw terminal : <= 6 mm ²
Cable stiffness	Flexible Rigid
Electrical insulation class	Class II
Height	83.5 mm
Width	45 mm
Depth	65 mm
Product weight	323 g

Environment

Standards	EN 60529 EN 60730-1
Ambient air temperature for operation	-20...50 °C
IP degree of protection	IP20 B

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0519 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

Contractual warranty

Period	18 months
--------	-----------