



Datasheet

RS Stock-No : 877-1047

RS Pro 5m Cable assembly with a 4 Pole Angled M12 Connector and an Unterminated End, 4 A, 250 V, IP67



Product Details

M12 Single Ended Cable Assembly

Brought to you under the trusted RS Brand, this range of M12 connector cable assemblies are commonly used in sensor and automation equipment. Boasting a high degree of environmental protection, they are ideal for industrial use. Fitted with a secure coupling nut, these RS M12 Connector Cable Assemblies are left un-terminated and partially stripped at one end, and are an ideal solution for when secure and reliable data transference is needed.

Features and Benefits:

- Wire is un-terminated and partially stripped
- Insulation Resistance $\geq 100 \text{ M}\Omega$
- Neoprene O-Ring
- Brass nickel plated coupling nut

RS M8 and M12



Specifications

Connector A	M12 Angled
Connector B	Unterminated
Length	5m
Number of Cores	4
Connector A Number of Contacts	4
Current Rating	4 A
Sheath Colour	Black
IP Rating	IP67
Voltage Rating	250 V
Cable Shape	Multicore
Cross Sectional Area	0.34 mm ²
Minimum Operating Temperature	-25°C
Outer Sheath Material	PVC
Maximum Operating Temperature	+75°C