

Datasheet

RS Pro New 500mm galvanised Steel Wire Hydraulic Hose Assembly, 155 bar Max Pressure, -40 to +121°C

RS Stock No: **110-2248**



Product Details

RS Pro hydraulic hose assembly of 500 mm, has maximum operating pressure of 155 bar. It has galvanised steel wire outer covering and high tensile steel wire reinforcing for durability. The hose assembly features straight G 3/8 female connector on both ends. It has operating temperature range of -40 to +121°C and is suitable for mineral oils, lubricating oils, water glycol and water-oil emulsion hydraulic fluids applications.

Features and Benefits

- Galvanised steel wire outer covering
- High tensile steel wire reinforcing
- Suitable for mineral oils, lubricating oils, water glycol, water-oil emulsion hydraulic fluids

Specifications:

| | |
|-------------------------------|-----------------------|
| Connector A - Angle | Straight |
| Connector A - Gender | Female |
| Connector A - Thread Size | 3/8 in |
| Connector A - Thread Standard | G |
| Connector A | Straight G 3/8 Female |
| Connector B - Angle | Straight |
| Connector B - Gender | Female |
| Connector B - Thread Size | 3/8 in |
| Connector B - Thread Standard | G |
| Connector B | Straight G 3/8 Female |
| Cover Material | Galvanised Steel Wire |
| Inner Hose Material | Synthetic Rubber |
| Inside Diameter | 3/8 in |
| Maximum Operating Pressure | 155 bar |
| Maximum Operating Temperature | +121°C |
| Minimum Operating Temperature | -40°C |
| Overall Length | 500 mm |
| Reinforcing Material | Steel |
| Standards Met | RoHS Compliant |