

## DIN rail connector - ME 6,2 TBUS-2 1,5/5-ST-3,81 GN - 2869728

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

DIN rail connector for DIN rail mounting. Universal for TBUS housing. Gold-plated contacts, 5-pos.




### Why buy this product

- For bridging the supply voltage
- One DIN rail connector for two MINI Analog modules
- Current carrying capacity of 8 A parallel to DIN rail and 2 A parallel to MINI Analog modules
- Reduced wiring effort
- Module replacement without interrupting the supply to the remaining modules (hot swappable)
- 



### Key commercial data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	 4 017918 983093
Weight per Piece (excluding packing)	4.6 g
Custom tariff number	85366990
Country of origin	Germany

### Technical data

Width	6.2 mm
Number of positions	5

### General

Color	green
-------	-------

### Dimensions

Width	6.2 mm
Pitch	3.81 mm

### Technical data

# DIN rail connector - ME 6,2 TBUS-2 1,5/5-ST-3,81 GN - 2869728

## Technical data

### Technical data

Connection in acc. with standard	CUL
Nominal voltage $U_N$	150 V
Nominal current $I_N$	8 A
Indicator1	CUL1
Number of positions	5

## Classifications

### eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27449001
eCl@ss 8.0	27182702

### ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC001031

### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

## Approvals

### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / EAC / EAC / cULus Recognized

---

#### Ex Approvals

---

# DIN rail connector - ME 6,2 TBUS-2 1,5/5-ST-3,81 GN - 2869728

## Approvals

Approvals submitted

### Approval details

UL Recognized		
	B	D
Nominal current I <sub>N</sub>	8 A	8 A
Nominal voltage U <sub>N</sub>	150 V	150 V

cUL Recognized		
	B	D
Nominal current I <sub>N</sub>	8 A	8 A
Nominal voltage U <sub>N</sub>	150 V	150 V

EAC
-----

EAC
-----

cULus Recognized
------------------