

## HALOLINE ECO 80 W 230 V R7S

HALOLINE ECO | Double ended halogen lamps with tube base



### Areas of application

- General illumination
- Entrance lighting
- Pathway lighting
- Outdoor applications only in suitable luminaires
- Traffic areas
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings

### Product benefits

- Brilliant ECO accent lighting
- Direct replacement for standard tubular halogen lamps
- Significantly lower CO<sub>2</sub> emissions
- Lower thermal output (compared with the standard reference product)
- No transformer required
- Contains no mercury

### Product features

- Average life: 2,000 h
- Dimmable
- Color rendering index R<sub>a</sub>: 100



# Product datasheet

## Technical data

### Electrical data

Nominal wattage	80.00 W
Nominal voltage	230 V
Rated wattage	80.00 W
Claimed equiv. conventional lamp power	100 W
Power factor $\lambda$	1.00

### Photometrical data

Nominal luminous flux	1400 lm
Color temperature	2950 K
Light color as per EN 12464-1	Warm White
Rated luminous flux	1400 lm
Color rendering index Ra	100
Lumen main.fact.at end of nom.life time	0.80

### Light technical data

Starting time	0.0 s
Warm-up time (60 %)	0.00 s

### Dimensions & weight



Diameter	12.0 mm
Overall length	74.9 mm
Length	80.3 mm
Outer bulb	T12

### Lifespan

Nominal lamp life time	2000 h
------------------------	--------

## Product datasheet

<b>Rated lamp life time</b>	2000 h
<b>Number of switching cycles</b>	50000 <sup>1)</sup>

<sup>1)</sup> At 1 min on / 3 min off

### Additional product data

<b>Base (standard designation)</b>	R7s
<b>Lamp mercury content</b>	0.0 mg
<b>Mercury-free</b>	Yes
<b>Footnote only for product</b>	Fuse protection with indicated values recommended acc. to IEC60357, EN60357/For outdoor applications and operation in damp locations special approved fixtures are required

### Capabilities

<b>Fuse, quick-acting</b>	2.0 A
<b>Burning position</b>	Any
<b>Dimmable</b>	Yes

### Certificates & standards

<b>Energy efficiency class</b>	D
<b>Energy consumption</b>	80 kWh/1000h


### Country specific categorizations

<b>ILCOS</b>	HDG-80-230-R7s-74,9
<b>Order reference</b>	64690 ECO 80W 2

### Light Distribution

---

## Product datasheet



---

### Spectral power distribution

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Volume	Gross weight
4008321327758	HALOLINE ECO 80 W 230 V R7S	Shipping carton box 20	92 mm x 77 mm x 112 mm	0.79 dm <sup>3</sup>	209.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.