



JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF26240-24B	LCD HIGH OUTPUT WHITE 11000°k RGB	1250 @ 0°C	505	5	30,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		METRIC THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION									
						MINIATURE COLD CATHODE FLUORESCENT LAMP									
A		DIM LINE CORRECT. AND 240+/-5.0 TO 240+/-3.0		10/17/00		DRAWN BY		APPVD BY DATE		SIZE		FSCM NO.		DRAWING NO.	
		RELEASED		5/22/00		L. WENGSTROM		FD 10/17/00		A		55335		BF26240-24B	
REV. NO.		DESCRIPTION/ECO NUMBER		APPVD DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE		RELEASED DATE		REVISION DATE		REV. NO. SHEET	
								NONE		5/22/00		10/17/00		A 1 OF 1	