



JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS)
BF22140-24B	LCD HIGH OUTPUT WHITE 8400°k RGB	730 @ 0°C	340	5	38,000 ± 10%	20,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		 THIRD ANGLE PROJECTION		<b>METRIC</b> DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>					
						TITLE <b>MINIATURE COLD CATHODE FLUORESCENT LAMP</b>					
<b>A</b> DIM LINE CORRECT. AND 140 +/- 5.0 TO 140 +/- 3.0 RELEASED		10/17/00 L. WENGSTROM		APPVD BY DATE FD 10/17/00		SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>BF22140-24B</b>			
REV. NO.		DESCRIPTION/ECO NUMBER		APPVD DATE		SCALE <b>NONE</b>		RELEASED DATE 6/7/00	REVISION DATE 10/17/00	REV. NO. <b>A</b>	SHEET <b>1 OF 1</b>