


Pin Spacing: 5.08mm  
 Orientation: Horizontal - Double Level Header  
 Clamp Type: –  
 Design: Modular - Open End



**PDSHxx-5.08**

**ELECTRICAL**

|  | Current | Voltage | Wire Range |
|--|---------|---------|------------|
|  | 12A     | 300V    | –          |
|  | 16A     | 450V    | –          |


**INSTALLATION DATA**

|            |   |                 |       |
|------------|---|-----------------|-------|
| Screw Size | – | PCB Hole Size   | 1.5mm |
| Torque     | – | Stripping Lgth. | –     |

**MATERIAL**

|                    |                       |          |                  |
|--------------------|-----------------------|----------|------------------|
| Body               | Polyamide             | Screw    | –                |
| Flammability Class | UL94V-0               | Terminal | Tin-Plated Brass |
| Temperature Limit  | 105°C UL<br>125°C IEC | Clamp    | –                |
| Color              | Green                 |          |                  |

Pin Spacing: 5.08mm  
 Orientation: Dual Row Vertical Header  
 Clamp Type: –  
 Design: Single Mold



**PDVxx-5.08**

**ELECTRICAL**

|  | Current | Voltage | Wire Range |
|--|---------|---------|------------|
|  | 12A     | 300V    | –          |
|  | 16A     | 450V    | –          |

**INSTALLATION DATA**

|            |   |                 |       |
|------------|---|-----------------|-------|
| Screw Size | – | PCB Hole Size   | 1.5mm |
| Torque     | – | Stripping Lgth. | –     |

**MATERIAL**

|                    |                       |          |                  |
|--------------------|-----------------------|----------|------------------|
| Body               | Polyamide             | Screw    | –                |
| Flammability Class | UL94V-0               | Terminal | Tin-Plated Brass |
| Temperature Limit  | 105°C UL<br>125°C IEC | Clamp    | –                |
| Color              | Green                 |          |                  |

| No. Poles | Cat. #      | Length (mm) | Std. Pk. |
|-----------|-------------|-------------|----------|
| 4         | PDSH02-5.08 | 12.7        | 100      |
| 6         | PDSH03-5.08 | 17.8        | 100      |
| 8         | PDSH04-5.08 | 22.9        | 50       |
| 10        | PDSH05-5.08 | 28.0        | 50       |
| 12        | PDSH06-5.08 | 33.0        | 50       |
| 14        | PDSH07-5.08 | 38.0        | 50       |
| 16        | PDSH08-5.08 | 43.2        | 50       |
| 18        | PDSH09-5.08 | 48.3        | 50       |
| 20        | PDSH10-5.08 | 53.3        | 50       |
| 22        | PDSH11-5.08 | 58.4        | 20       |
| 24        | PDSH12-5.08 | 63.5        | 20       |
| 26        | PDSH13-5.08 | 68.6        | 20       |
| 28        | PDSH14-5.08 | 73.7        | 20       |
| 30        | PDSH15-5.08 | 78.7        | 20       |
| 32        | PDSH16-5.08 | 83.8        | 20       |
| 34        | PDSH17-5.08 | 89.9        | 20       |
| 36        | PDSH18-5.08 | 94.0        | 20       |
| 38        | PDSH19-5.08 | 99.1        | 20       |
| 40        | PDSH20-5.08 | 104.1       | 10       |
| 42        | PDSH21-5.08 | 109.2       | 10       |
| 44        | PDSH22-5.08 | 114.3       | 10       |
| 46        | PDSH23-5.08 | 119.4       | 10       |
| 48        | PDSH24-5.08 | 124.5       | 10       |

| No. Poles | Cat. #     | Length (mm) | Std. Pk. |
|-----------|------------|-------------|----------|
| 2         | PDV02-5.08 | 12.2        | 100      |
| 3         | PDV03-5.08 | 17.2        | 100      |
| 4         | PDV04-5.08 | 22.3        | 50       |
| 5         | PDV05-5.08 | 27.4        | 50       |
| 6         | PDV06-5.08 | 32.5        | 50       |
| 7         | PDV07-5.08 | 37.6        | 50       |
| 8         | PDV08-5.08 | 42.6        | 50       |
| 9         | PDV09-5.08 | 47.7        | 50       |
| 10        | PDV10-5.08 | 52.8        | 50       |
| 11        | PDV11-5.08 | 57.9        | 50       |
| 12        | PDV12-5.08 | 63.0        | 50       |

