

## Start Waterproof LED G3 fixed output

*START Waterproof Twin 1500 IP65 7100lm 865*  
0067966



### Product features

- Start Waterproof, integrated LED weatherproof luminaire, with UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing, Polycarbonate diffuser, 7050 lm, 58 W, 122 lm/W, 6500 K, drive current 700 mA, non dimmable, CRI80, IP65, IK08, Class I, nominal average lifetime (h): 50000, 1578 mm x 110 mm x 78 mm, energy class: A++ A+ A, D-mark



## PRODUCT OVERVIEW

IPC Code	0067966
Product name	START Waterproof Twin 1500 IP65 7100lm 865
Technology	LED
Housing	Polycarbonate
Mount	Ceiling Mounting and Suspended Mounting
Fixture rating	Enclosed
General application	Logistics & Industry
Certifications	EUNEW009
ETIM Class	EC002892
Fixture luminous flux (lm)	7050
Luminaire efficacy (lm/W)	122
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Photobiological Risk Group	RG1
Total power consumption (W)	58
Electrical protection	Class I
Control gear type	Electronic (constant current)
Dimmable	No
Average life (Nominal) (h)	50000
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288679662
Lamps	Yes
Included lamp	INTEGRATED LED

## DATA TABLE

### General data

IPC Code	0067966
Product name	START Waterproof Twin 1500 IP65 7100lm 865
Technology	LED
Housing	Polycarbonate
Mount	Ceiling Mounting and Suspended Mounting

## Start Waterproof LED G3 fixed output *START Waterproof Twin 1500 IP65 7100lm 865* 0067966

Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Certifications	EUNEW009
ETIM Class	EC002892

### Optical data

Fixture luminous flux (lm)	7050
Luminaire efficacy (lm/W)	122
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Distribution type	Direct
Photobiological Risk Group	RG1

### Electrical data

Total power consumption (W)	58
Mains voltage (V)	220-240V~
Lamp power factor	0.91
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	20
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic (constant current)
Dimmable	No
Drive current (mA)	700
Nominal Frequency (Hz)	50/60Hz

### Lifetime data

Lumen maintenance - L70 B50	60000
Lumen maintenance - L70 B20	60000
Lumen maintenance - L70 B10	60000
Lumen maintenance - L80 B50	60000
Lumen maintenance - L80 B20	60000
Lumen maintenance - L80 B10	60000
Lumen maintenance - L90 B50	59000
Lumen maintenance - L90 B20	53000
Lumen maintenance - L90 B10	50000
Average life (Nominal) (h)	50000

### Physical data

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Clear
Diffuser material	Polycarbonate
Nominal Product Length (mm)	1578
Nominal Product Width (mm)	110
Nominal Product Height (mm)	78

## Start Waterproof LED G3 fixed output START Waterproof Twin 1500 IP65 7100lm 865 0067966

Weight (kg)	2.42
-------------	------


### Packaging

Single packaging type	Carton
Product EAN number	5410288679662
Packaging single length / height (cm)	167.2
Packaging single width (cm)	11.6
Packaging single depth (cm)	8.4
DUN14 (outer)	05410288679662
Units per outer package	1
Packaging outer length / height (cm)	167.2
Packaging outer width (cm)	11.6
Packaging outer depth (cm)	8.4

### Safety data

Dry applications use only	No
---------------------------	----

## PHOTOMETRY




Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam diameter [ft]	Illuminance [lx]
0.5	1.14	1.55	5.08	9066
	1.55	2.07	6.79	1299
1.0	2.28	3.10	10.17	2266
	3.10	4.12	13.53	332
1.5	3.43	4.66	15.29	1007
	4.66	6.21	20.37	164
2.0	4.57	6.21	20.37	587
	6.21	8.28	27.17	81
2.5	5.71	7.76	25.46	383
	7.76	10.41	34.31	84
3.0	6.85	9.31	30.54	282
	9.31	12.46	40.88	78


## TECHNICAL DRAWINGS




## Start Waterproof LED G3 fixed output *START Waterproof Twin 1500 IP65 7100lm 865* 0067966


**SYLVANIA** 0067966


 This luminaire contains built-in LED lamps

 } LED


The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built-in LED lamps

 } LED

The lamps cannot be changed in the luminaire.

**SYLVANIA** 0067966 

874/2012