

LIGHTS

9490

Remote Area Lighting System

Save as PDF



9490 Remote Area Lighting System

Up to 6,000 lumens (calculated)



Light Source

LED Type	LED Life	Tested Lumen Value
High Flux LED	50000	(Low) 6000 (High)
Lamp Heads	Number of LEDs	Beam Spread
1	10	125
Brightness Settings	IP Rating (Ingress Protection)	
0		

Power Source

Battery Type	Battery Burn Time	Battery Charging Time	Battery Life

Dimensions & Weight

Head Length	Head Width	Head Depth
20.9cm.	14.6cm.	5.7cm.
Width Closed	Length Closed	Height Closed
16.5cm.	50.8cm.	28.6cm.
Mast Height Extended	Cord Length	Weight
182.8 cm.	0cm.	14.51kg.

Materials

Head	Body	Mast
Aluminum	Polypropylene	Aluminium
Lens	Switch Type	

TIME		TIME	
12v Rechargeable, Sealed Lead Acid (SLA)	24 (Low) 3.5 (High)	8 hrs. from full discharge	500
Low Battery Warning	12V Primary Sockets	12V Auxiliary Sockets	
Full-time battery level display and low battery warning (visible flashing)	1	0	
Watts	Voltage		
0	12		

Polycarbonate	Silicone rubber keypad
---------------	------------------------

Configuration

Cat. #	Description
9490	9490 Remote Area Lighting System

9490 Remote Area Lighting System Accessories

No accessories are currently available for this product